

P/N MS18065-19

Military-Fasteners.com

Description

Fastener Length: 5/16", Thread: 10-32, Head Width: 3/32", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS1806519
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-026-4368
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS18065-19 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS18065-19</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.