

Description

Fastener Length: 7/16", Thread: 10-32, Head Width: 3/32", Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806525
Minimum Qty (MOQ):	35 EA
NSN:	5305-01-298-6288
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS18065-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.335 Inches Minimum And 0.355 Inches Maximum
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.095 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.