

Description

Fastener Length: 3/8", Thread: 1/4-24, Head Width: 5/32", Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806527
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-291-6106
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS18065-27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.234 Inches Nominal
Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	33.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Aisi G40320 Assn Std 1st Material Response Overall Or Aisi G40370 Assn Std 2nd Material Response Overall Or Aisi G41370 Assn Std 3rd Material Response Overall Or Aisi G41400 Assn Std 4th Material Response Overall Or Aisi G86300 Assn Std 5th Material Response Overall Or Aisi G87400 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Specification/standard Data:	96906-ms18065 Government Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.