

Description

Fastener Length: 7/16", Thread: 8-32, Head Width: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS1806530 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-01-314-3026 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N MS18065-30 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.164 Inches |
| Width Across Flats: | 0.062 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 35.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Material: | Plastic Polyamide Locking Feature |
| Material: | Steel Comp 4032 Fastener Or Steel Comp 4037 Fastener Or Steel Comp 4137 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8740 Fastener |
| Surface Treatment: | Cadmium Fastener And Chromate Fastener |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Style And 1 Type |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.