

Description

Fastener Length: 7/16", Thread: 8-32, Head Width: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806530
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-314-3026
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS18065-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.062 Inches Nominal
Thread Quantity Per Inch:	32
Hardness Rating:	35.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 4032 Fastener Or Steel Comp 4037 Fastener Or Steel Comp 4137 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8740 Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Style And 1 Type

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.