

**Description**

Fastener Length: 7/16", Thread: 8-32, Head Width: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1806530
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-314-3026
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N MS18065-30 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Width Across Flats:</b>	0.062 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	35.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Material:</b>	Plastic Polyamide Locking Feature
<b>Material:</b>	Steel Comp 4032 Fastener Or Steel Comp 4037 Fastener Or Steel Comp 4137 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8740 Fastener
<b>Surface Treatment:</b>	Cadmium Fastener And Chromate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Style And 1 Type

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.