

## P/N MS18065-68

## **Description**

Fastener Length: 63/64", Thread: 10-32, Head Width: 3/32", Thread Length: 63/64

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS1806568

Minimum Qty (MOQ): 10

NSN: 5305-01-116-7356

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS18065-68 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.980 Inches Minimum And 1.020 Inches Maximum
Fastener Length:	0.980 Inches Minimum And 1.020 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Nominal
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type Or 1 Style

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS18065-68">https://military-fasteners.com/screws/machine+screws/MS18065-68</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS18065-68">https://military-fasteners.com/screws/machine+screws/MS18065-68</a> and selecting the quantity you