

**Description**

Fastener Length: 3/16", Thread: 8-32, Head Width: 5/64", Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS180657                                  |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-408-6526                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS18065-7 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.178 Inches Minimum And 0.198 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.178 Inches Minimum And 0.198 Inches Maximum  |
| <b>Head Style:</b>                                    | Headless (setscrew)  |
| <b>Locking Feature:</b>                               | Pellet Threads Or Strip Threads  |
| <b>Point Style:</b>                                   | Flat   |
| <b>Internal Drive Style:</b>                          | Hexagon  |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches   |
| <b>Width Across Flats:</b>                            | 0.078 Inches Minimum And 0.079 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Hardness Rating:</b>                               | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall  |
| <b>Material:</b>                                      | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4032 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,c1 3 Fed Spec All Treatment Responses Overall  |
| <b>Thread Series Designator:</b>                      | Unc  |
| <b>Nondefinitive Spec/std Data:</b>                   | 1 Type And 1 Style   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18065-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.