



Military-Fasteners.com

P/N MS18066-12

Description

Fastener Length: 1/4", Thread: 8-32, Head Width: 5/64", Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806612
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-055-3771
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS18066-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Fastener Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.164 Inches
Width Across Flats:	0.078 Inches Minimum And 0.079 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18066-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.