

Description

Fastener Length: 5/8", Thread: 1/2-20, Head Width: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1806653
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-354-3718
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS18066-53 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.250 Inches Minimum And 0.252 Inches Maximum
Thread Quantity Per Inch:	20
Hardness Rating:	35.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
Material:	Plastic Polyamide Locking Featuresteel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 316 Fastener
Material Document And Classification:	66 Fed Std All Material Responses Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS18066-53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.