

**Description**

Fastener Length: 5/8", Thread: 1/2-20, Head Width: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS1806653
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-354-3718
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS18066-53 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Width Across Flats:</b>	0.250 Inches Minimum And 0.252 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Hardness Rating:</b>	35.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener
<b>Material:</b>	Plastic Polyamide Locking Featuresteel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 316 Fastener
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Fastener
<b>Surface Treatment:</b>	Passivate Fastener
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	1 Type And 1 Style

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS18066-53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.