

Description

Fastener Length: 5/8", Thread: 1/2-20, Head Width: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS1806653 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-354-3718 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS18066-53 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.500 Inches |
| Width Across Flats: | 0.250 Inches Minimum And 0.252 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Hardness Rating: | 35.0 Rockwell C Minimum Fastener And 45.0 Rockwell C Maximum Fastener |
| Material: | Plastic Polyamide Locking Featuresteel Comp 302 Fastener Or Steel Comp 303 Fastener Or Steel Comp 304 Fastener Or Steel Comp 316 Fastener |
| Material Document And Classification: | 66 Fed Std All Material Responses Fastener |
| Surface Treatment: | Passivate Fastener |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Fastener |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 1 Style |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS18066-53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.