

Description

Fastener Length: 1-3/16", Thread: 10-32, Thread Length: 1-3/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | MS18211105F |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-022-8054 |
| Schedule B: | 3926.90.8500 |
| ECCN: | EAR99 |
| National Motor Freight: | 000000, No Nmfc Freight Description |



* See page 2 for technical characteristics

P/N MS18211-105F Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.043 Inches Minimum And 1.167 Inches Maximum |
| Fastener Length: | 1.188 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.333 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Plastic Polyhexamethylene Amide |
| Screw Material Document And Classification: | Mil-m-20693,ty 1 Mil Spec Single Material Response |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 3s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18211-105F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.