

Description

Fastener Length: 19/32", Thread: 1/4-28, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS18211126F
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-119-7574
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N MS18211-126F Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.523 Inches Minimum And 0.554 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.442 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Plastic Polyhexamethylene Amide
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 3s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18211-126F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.