

P/N MS18211-28C

Description

Fastener Length: 11/64", Thread: 4-40, Thread Length: 1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS1821128C
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-433-3766
Schedule B:	3926.90.8500
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N MS18211-28C Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.058 Inches Minimum And 0.139 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.191 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Plastic Polyhexamethylene Amide
Screw Material Document And Classification:	Mil-m-20693,comp A,ty 1 Mil Spec Single Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 3s Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS18211-28C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS18211-28C and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS18211-28C and selecting the quantity you want then click "add to cart".