

Description

Fastener Length: 9/32", Thread: 4-40, Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS1821214
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-833-8626
Schedule B:	3926.90.8500
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N MS18212-14 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.262 Inches Minimum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.058 Inches Minimum And 0.068 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Material:	Plastic Polyhexamethylene Amide
Screw Material Document And Classification:	Mil-m-20693 Ty 1 Mil Spec Single Material Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18212-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.