

Description

Fastener Length: 3/4", Thread: 4-40, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS1821219 |
| Minimum Qty (MOQ): | 100 EA |
| NSN: | 5305-00-833-8650 |
| Schedule B: | 3926.90.4590 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS18212-19 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.700 Inches Minimum |
| Fastener Length: | 0.719 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.205 Inches Minimum And 0.219 Inches Maximum |
| Head Height: | 0.058 Inches Minimum And 0.068 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Screw Material: | Plastic Polyhexamethylene Amide |
| Screw Material Document And Classification: | Mil-m-20693 Ty 1 Mil Spec Single Material Response |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18212-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.