

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS1821230 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-582-6151 |
| Schedule B: | 3926.90.4590 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS18212-30 Specifications

| | |
|--|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.256 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.072 Inches Minimum And 0.082 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Plastic Polyhexamethylene Amide |
| Screw Material Document And Classification: | Mil-m-20693,comp A,ty 1 Mil Spec Single Material Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 8s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS18212-30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.