

P/N MS18212-45

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS1821245
Minimum Qty (MOQ): 20 EA

NSN: 5305-00-078-0226

Schedule B: 3926.90.4590

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N MS18212-45 Specifications

| Thread Class: | 2a |
|---|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Minimum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.085 Inches Minimum And 0.096 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Plastic Polyhexamethylene Amide |
| Screw Material Document And Classification: | Mil-m-20693 Mil Spec Single Material Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 9s Style |
| Departure From Cited Designator: | As Modified By Material |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS18212-45 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS18212-45 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS18212-45 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms18212-45 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms18212-45 and selecting the quantity you want then complete your order.