

P/N MS20002C16

Description

Fits size: 1", countersunk, high strength, cadmium plated alloy steel, MS20002 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS20002C16

Minimum Qty (MOQ): 25

NSN: 5310-00-596-1774

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









^{*} See page 2 for technical characteristics

P/N MS20002C16 Specifications

Hole Diameter:	1.010 Inches Minimum And 1.025 Inches Maximum
Outside Diameter:	1.615 Inches Minimum And 1.635 Inches Maximum
Recess Diameter:	1.140 Inches Minimum And 1.160 Inches Maximum
Material Thickness:	0.068 Inches Minimum And 0.088 Inches Maximum
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed

How to Order

Order this recessed washer from our inventory online by visiting https://military-fasteners.com/washers/recessed+washers/MS20002C16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.