

Description

Hole Diameter: 1-1/8", MS20002 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS20002-C18](#)

SKU / Model:	MS20002C18
Minimum Qty (MOQ):	20
NSN:	5310-00-209-3445
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS20002C18 Specifications

Hole Diameter:	1.135 Inches Minimum And 1.150 Inches Maximum
Outside Diameter:	1.865 Inches Minimum And 1.885 Inches Maximum
Recess Diameter:	1.265 Inches Minimum And 1.285 Inches Maximum
Recess Depth:	0.067 Inches Nominal
Material Thickness:	0.068 Inches Minimum And 0.088 Inches Maximum
Minimum Tensile Strength:	125 Pounds Per Square Inch
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed
Specification/standard Data:	80205-nas143 Professional/Industrial Association Standard

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS20002C18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.