

**Description**

Hole Diameter: 1-1/8", MS20002 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS20002-C18](#)

SKU / Model:	MS20002C18
Minimum Qty (MOQ):	20
NSN:	5310-00-209-3445
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS20002C18 Specifications

<b>Hole Diameter:</b>	1.135 Inches Minimum And 1.150 Inches Maximum
<b>Outside Diameter:</b>	1.865 Inches Minimum And 1.885 Inches Maximum
<b>Recess Diameter:</b>	1.265 Inches Minimum And 1.285 Inches Maximum
<b>Recess Depth:</b>	0.067 Inches Nominal
<b>Material Thickness:</b>	0.068 Inches Minimum And 0.088 Inches Maximum
<b>Minimum Tensile Strength:</b>	125 Pounds Per Square Inch
<b>Recess Angle:</b>	89.0 Degrees Minimum And 91.0 Degrees Maximum
<b>Material:</b>	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Style Designator:</b>	Recessed
<b>Specification/standard Data:</b>	80205-nas143 Professional/Industrial Association Standard

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/MS20002C18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.