

Description

to fit size: 1-1/4", countersunk, high strength, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20002-C20](#)

SKU / Model:	MS20002C20
Minimum Qty (MOQ):	25
NSN:	5310-00-149-9123
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N MS20002C20 Specifications

Hole Diameter:	1.260 Inches Minimum And 1.275 Inches Maximum
Outside Diameter:	2.115 Inches Minimum And 2.135 Inches Maximum
Recess Diameter:	1.427 Inches Minimum And 1.447 Inches Maximum
Material Thickness:	0.084 Inches Minimum And 0.104 Inches Maximum
Minimum Tensile Strength:	125 Pounds Per Square Inch
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Special Features:	Heat Treatment Per Mil-h-6875
Material:	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS20002C20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.