

Description

Hole Diameter: 1-1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS20002C24 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5310-00-262-5451 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |

NO IMAGE
AVAILABLE

P/N MS20002C24 Specifications

| | |
|---|---|
| Hole Diameter: | 1.510 Inches Minimum And 1.525 Inches Maximum |
| Outside Diameter: | 2.490 Inches Minimum And 2.510 Inches Maximum |
| Recess Diameter: | 1.677 Inches Minimum And 1.697 Inches Maximum |
| Material Thickness: | 0.084 Inches Minimum And 0.104 Inches Maximum |
| Recess Angle: | 89.0 Degrees Minimum And 91.0 Degrees Maximum |
| Material: | Steel Comp 1330 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |
| Style Designator: | Recessed |

How to Order

Order this washer from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20002C24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.