

Description

fit size: 1/4", countersunk, high strength, cadmium plated alloy steel, MS20002 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20002C4
Minimum Qty (MOQ):	100
NSN:	5310-00-596-1766
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS20002C4 Specifications

Hole Diameter:	0.252 Inches Minimum And 0.260 Inches Maximum
Outside Diameter:	0.521 Inches Minimum And 0.541 Inches Maximum
Recess Diameter:	0.334 Inches Minimum And 0.344 Inches Maximum
Material Thickness:	0.068 Inches Minimum And 0.088 Inches Maximum
Recess Angle:	89.0 Degrees Minimum And 91.0 Degrees Maximum
Material:	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS20002C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.