

Description

size: 1/2, countersunk, high strength, cadmium plated alloy steel, MS20002 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20002-C8](#)

SKU / Model:	MS20002C8
Minimum Qty (MOQ):	100
NSN:	5310-00-149-9116
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS20002C8 Specifications

Hole Diameter:	0.504 Inches Minimum And 0.515 Inches Maximum
Outside Diameter:	0.875 Inches Nominal
Recess Diameter:	0.604 Inches Minimum And 0.620 Inches Maximum
Material Thickness:	0.078 Inches Nominal
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Recess Angle:	90.0 Degrees Nominal
Material:	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
Material:	Steel Comp 1330 Or Steel Comp 4130 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	15 Recessed
Style Designator:	Recessed

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS20002C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.