

Description

size: 1/2, countersunk, high strength, cadmium plated alloy steel, MS20002 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS20002-C8](#)

| | |
|-------------------------|---|
| SKU / Model: | MS20002C8 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-00-149-9116 |
| Schedule B: | 7318.22.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N MS20002C8 Specifications

| | |
|---|---|
| Hole Diameter: | 0.504 Inches Minimum And 0.515 Inches Maximum |
| Outside Diameter: | 0.875 Inches Nominal |
| Recess Diameter: | 0.604 Inches Minimum And 0.620 Inches Maximum |
| Material Thickness: | 0.078 Inches Nominal |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Recess Angle: | 90.0 Degrees Nominal |
| Material: | Steel Comp 1330 Overall Or Steel Comp 4130 Overall |
| Material: | Steel Comp 1330 Or Steel Comp 4130 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | 15 Recessed |
| Style Designator: | Recessed |

How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS20002C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.