

**Description**

size: 9/16", countersunk, high strength, cadmium plated alloy steel, MS20002 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**[MS20002-C9](#)

SKU / Model:	MS20002C9
Minimum Qty (MOQ):	50
NSN:	5310-00-596-1712
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS20002C9 Specifications

<b>Hole Diameter:</b>	0.568 Inches Minimum And 0.579 Inches Maximum
<b>Outside Diameter:</b>	0.958 Inches Minimum And 0.978 Inches Maximum
<b>Recess Diameter:</b>	0.667 Inches Minimum And 0.687 Inches Maximum
<b>Material Thickness:</b>	0.068 Inches Minimum And 0.088 Inches Maximum
<b>Recess Angle:</b>	89.0 Degrees Minimum And 91.0 Degrees Maximum
<b>Material:</b>	Steel Comp 1330 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	15 Recessed
<b>Style Designator:</b>	Recessed

## How to Order

Order this recessed washer from our inventory online by visiting <https://military-fasteners.com/washers/recessed+washers/MS20002C9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.