

P/N MS20004-21

Description

Fastener Length: 1-13/16", Thread: 1/4-28, Head Width: 3/16", Thread Length: 33/64", MS20004 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS2000421
Minimum Qty (MOQ):	5
NSN:	5306-00-420-6475
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS20004-21 Specifications

Thread Direction: Right-hand Thread Length: 0.475 Inches Minimum And 0.525 Inches Maximum Fastener Length: 1.797 Inches Minimum And 1.827 Inches Maximum Head Style: Undercut Pan No. 2 Head Diameter: 0.428 Inches Minimum And 0.438 Inches Maximum Head Height: 0.250 Inches Mominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Inches Inc		
Thread Length: 0.475 Inches Minimum And 0.525 Inches Maximum 1.797 Inches Minimum And 1.827 Inches Maximum Head Style: Undercut Pan No. 2 Head Diameter: 0.428 Inches Minimum And 0.438 Inches Maximum Head Height: 0.250 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Class:	3a
Fastener Length: 1.797 Inches Minimum And 1.827 Inches Maximum Head Style: Undercut Pan No. 2 Head Diameter: 0.428 Inches Minimum And 0.438 Inches Maximum Head Height: 0.250 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Classification: Response Overall Or Mil-s-6098 Mil Spec 1st Material Response Overall Or Mil-s-60049 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Cadmium Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Direction:	Right-hand
Head Style: Undercut Pan No. 2 Head Diameter: 0.428 Inches Minimum And 0.438 Inches Maximum Head Height: 0.250 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Length:	0.475 Inches Minimum And 0.525 Inches Maximum
Head Diameter: 0.428 Inches Minimum And 0.438 Inches Maximum Head Height: 0.250 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Fastener Length:	1.797 Inches Minimum And 1.827 Inches Maximum
Head Height: 0.250 Inches Nominal Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 0q-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Undercut Pan No. 2
Internal Drive Style: Hexagon Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Sp	Head Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Height:	0.250 Inches Nominal
Width Across Flats: 0.188 Inches Minimum And 0.190 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Hexagon
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Hardness Rating: 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Thread Quantity Per Inch:	28
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	
And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf		Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20004-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.