

Description

Fastener Length: 1-15/16", Thread: 1/4-28, Head Width: 3/16", Thread Length: 33/64", MS20004 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000423
Minimum Qty (MOQ):	10
NSN:	5306-01-064-7763
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20004-23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.475 Inches Minimum And 0.525 Inches Maximum
Fastener Length:	1.922 Inches Minimum And 1.952 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Minimum And 0.190 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20004-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.