

**Description**

Fastener Length: 2-29/32", Thread: 1/4-28, Head Width: 3/16", Thread Length: 15/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2000439
Minimum Qty (MOQ):	1
NSN:	5306-01-260-1811
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS20004-39 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.475 Inches Minimum
<b>Fastener Length:</b>	2.912 Inches Nominal
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	0.428 Inches Minimum And 0.438 Inches Maximum
<b>Head Height:</b>	0.250 Inches Minimum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.188 Inches Minimum And 0.190 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Chromate Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty li,cls 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20004-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.