

P/N MS20004H9

Description

Fastener Length: 1", Hole Diameter: 1/32", Thread: 1/4-28, Head Width: 3/16", Thread Length: 15/32", bevel conical head, drilled, MS20004 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS20004H9

Minimum Qty (MOQ):

NSN: 5306-01-411-0834

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)





^{*} See page 2 for technical characteristics

P/N MS20004H9 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.475 Inches Minimum |
| Fastener Length: | 1.062 Inches Nominal |
| Head Style: | Bevel-conical |
| Head Diameter: | 0.428 Inches Minimum And 0.438 Inches Maximum |
| Head Height: | 0.250 Inches Nominal |
| Hole Diameter: | 0.037 Inches Minimum And 0.042 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Width Across Flats: | 0.1880 Inches Minimum And 0.1900 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Hole Configuration Style: | Round Internal Hexagon |
| Material: | Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20004H9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.