

Description

Fastener Length: 1", Hole Diameter: 1/32", Thread: 1/4-28, Head Width: 3/16", Thread Length: 15/32", bevel conical head, drilled, MS20004 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS20004H9
Minimum Qty (MOQ):	5
NSN:	5306-01-411-0834
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20004H9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.475 Inches Minimum
Fastener Length:	1.062 Inches Nominal
Head Style:	Bevel-conical
Head Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Head Height:	0.250 Inches Nominal
Hole Diameter:	0.037 Inches Minimum And 0.042 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.1880 Inches Minimum And 0.1900 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Round Internal Hexagon
Material:	Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20004H9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.