

Description

length: 1-3/16", grip: 5/8", thread: 5/16-24, internal wrenching, cadmium plated alloy steel, MS20005 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000510
Minimum Qty (MOQ):	10
NSN:	5306-01-408-4049
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20005-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.537 Inches Minimum
Fastener Length:	1.173 Inches Minimum And 1.203 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.