



★ FASTENERS

Military-Fasteners.com

P/N MS20005-12

## Description

length: 1-5/16", grip: 3/4", thread: 5/16-24, internal wrenching, cadmium plated alloy steel, MS20005 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS2000512                                 |
| Minimum Qty (MOQ):      | 5                                         |
| NSN:                    | 5306-00-638-3153                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS20005-12 Specifications

|                                  |                                                                     |
|----------------------------------|---------------------------------------------------------------------|
| <b>Thread Class:</b>             | 3a                                                                  |
| <b>Thread Direction:</b>         | Right-hand                                                          |
| <b>Thread Length:</b>            | 0.562 Inches Minimum                                                |
| <b>Fastener Length:</b>          | 1.312 Inches Nominal                                                |
| <b>Head Diameter:</b>            | 0.521 Inches Minimum And 0.531 Inches Maximum                       |
| <b>Head Height:</b>              | 0.312 Inches Nominal                                                |
| <b>Internal Drive Style:</b>     | Hexagon                                                             |
| <b>Nominal Thread Diameter:</b>  | 0.312 Inches                                                        |
| <b>Width Across Flats:</b>       | 0.219 Inches Minimum And 0.221 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b> | 24                                                                  |
| <b>Minimum Tensile Strength:</b> | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>          | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                 | Steel Overall                                                       |
| <b>Surface Treatment:</b>        | Cadmium Overall                                                     |
| <b>Thread Series Designator:</b> | Unjf                                                                |

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.