

**Description**

length: 1-7/16", grip: 7/8", thread: 5/16-24, internal wrenching, cadmium plated alloy steel, MS20005 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2000514
Minimum Qty (MOQ):	5
NSN:	5306-00-206-1363
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS20005-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.563 Inches Minimum
<b>Fastener Length:</b>	1.438 Inches Nominal
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	0.521 Inches Minimum And 0.531 Inches Maximum
<b>Head Height:</b>	0.312 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Width Across Flats:</b>	0.219 Inches Minimum And 0.221 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall Or Chromium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.