

## P/N MS20005-16

### **Description**

length: 1-9/16", grip: 1", thread: 5/16-24, internal wrenching, cadmium plated alloy steel, MS20005 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS2000516

Minimum Qty (MOQ):

NSN: 5306-00-207-1070

Schedule B: 7318.15.2000

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS20005-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Nominal
Fastener Length:	1.562 Inches Nominal
Head Style:	Bevel-conical
Head Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

## **How to Order**

Order this internal wrenching bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-16">https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.