

Description

MS20005-19 Internal Wrenching Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2000519
Minimum Qty (MOQ):	2
NSN:	5306-00-639-1738
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS20005-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.538 Inches Minimum And 0.588 Inches Maximum
Fastener Length:	1.735 Inches Minimum And 1.765 Inches Maximum
Head Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.302 Inches Minimum And 0.322 Inches Maximum
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.