

P/N MS20005-20

Description

length: 1-13/16", grip: 1-1/4", thread: 5/16-24, internal wrenching bolt - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000520
Minimum Qty (MOQ):	8
NSN:	5306-01-362-0710
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS20005-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.521 Inches Minimum And 0.531 Inches Maximum
Fastener Length:	1.797 Inches Minimum And 1.827 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-20 and selecting the