

P/N MS20005-25

Description

length: 2-1/16", grip: 1-9/16", thread: 5/16-24, internal wrenching bolt, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2000525

Minimum Qty (MOQ):

NSN: 5306-00-207-7979

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N MS20005-25 Specifications

Thread Class: 3a	Ba
Thread Direction:	Right-hand
Thread Length: 0.	0.537 Inches Minimum And 0.587 Inches Maximum
Fastener Length: 2.	2.110 Inches Minimum And 2.140 Inches Maximum
Head Diameter: 0.	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height: 0.	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter: 0.	0.312 Inches
Width Across Flats: 0.	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch: 24	24
Minimum Tensile Strength: 10	160000 Pounds Per Square Inch
Hardness Rating: 34	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: St	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment: Co	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.