

P/N MS20005-30

Description

Fastener Length: 2-29/64", Thread: 1/4-24, Head Width: 7/32", Thread Length: 37/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000530
Minimum Qty (MOQ):	1
NSN:	5306-00-206-2685
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS20005-30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.533 Inches Minimum And 0.588 Inches Maximum
Fastener Length:	2.418 Inches Minimum And 2.453 Inches Maximum
Head Style:	Bevel-conical Service Control of the
Head Diameter:	0.526 Inches Nominal
Head Height:	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.2200 Inches Nominal
Thread Quantity Per Inch:	24
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material
Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-30 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.