

P/N MS20005-36

Description

length: 2-13/16", grip: 2-1/4", thread: 5/16-24, internal wrenching, cadmium plated alloy steel, MS20005 series bolt

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS2000536

Minimum Qty (MOQ): 5

NSN: 5306-00-639-1727

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS20005-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Nominal
Fastener Length:	2.812 Inches Nominal
Head Style:	Bevel-conical Service Control of the
Head Diameter:	0.521 Inches Minimum And 0.531 Inches Maximum
Head Height:	0.312 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20005-36 and selecting the