

**Description**

length: 1-9/16", thread: 3/8-24, internal wrenching, cadmium plated alloy steel, MS20006 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2000614
Minimum Qty (MOQ):	5
NSN:	5306-01-436-9049
Schedule B:	7318.15.2000
ECCN:	9A991.d
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS20006-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.677 Inches Nominal
<b>Fastener Length:</b>	1.562 Inches Nominal
<b>Head Style:</b>	Bevel-conical
<b>Head Diameter:</b>	0.639 Inches Minimum And 0.649 Inches Maximum
<b>Head Height:</b>	0.375 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Width Across Flats:</b>	0.3130 Inches Minimum And 0.3150 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	15200 Pounds Per Square Inch
<b>Hardness Rating:</b>	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty2cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	96906-ms20004 Government Standard

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.