

Description

length: 1-9/16", thread: 3/8-24, internal wrenching, cadmium plated alloy steel, MS20006 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000614
Minimum Qty (MOQ):	5
NSN:	5306-01-436-9049
Schedule B:	7318.15.2000
ECCN:	9A991.d
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS20006-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.677 Inches Nominal
Fastener Length:	1.562 Inches Nominal
Head Style:	Bevel-conical
Head Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Head Height:	0.375 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.3130 Inches Minimum And 0.3150 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	15200 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms20004 Government Standard

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.