

**Description**

Fastener Length: 1-13/16", Thread: 3/8-24, Head Width: 5/16", Thread Length: 45/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | MS2000618        |
| Minimum Qty (MOQ): | 2                |
| NSN:               | 5306-00-206-0804 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N MS20006-18 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.662 Inches Minimum And 0.712 Inches Maximum   |
| <b>Fastener Length:</b>                               | 1.797 Inches Minimum And 1.827 Inches Maximum   |
| <b>Head Style:</b>                                    | Bevel-conical   |
| <b>Head Diameter:</b>                                 | 0.639 Inches Minimum And 0.649 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.375 Inches Nominal  |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Width Across Flats:</b>                            | 0.313 Inches Minimum And 0.315 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty2 Cl3 Fed Spec All Treatment Responses Overall   |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.