

Description

Fastener Length: 2-1/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 21/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2000625
Minimum Qty (MOQ):	5
NSN:	5306-01-482-7881
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS20006-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.663 Inches Nominal
Fastener Length:	2.235 Inches Minimum And 2.265 Inches Maximum
Head Style:	Bevel-conical
Head Diameter:	0.520 Inches Nominal
Head Height:	0.375 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4340 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, CI 2, Ty 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms20006 Government Specification

How to Order

Order this internal wrenching bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.