

P/N MS20006-25

Military-Fasteners.com

Description

Fastener Length: 2-1/4", Thread: 3/8-24, Head Width: 5/16", Thread Length: 21/32

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS2000625 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-482-7881 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS20006-25 Specifications

| Thread Class: | За |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.663 Inches Nominal |
| Fastener Length: | 2.235 Inches Minimum And 2.265 Inches Maximum |
| Head Style: | Bevel-conical |
| Head Diameter: | 0.520 Inches Nominal |
| Head Height: | 0.375 Inches Nominal |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.313 Inches Minimum And 0.315 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4340 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Cl 2, Ty 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 96906-ms20006 Government Specification |

How to Order

Order this internal wrenching bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-25</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.