

P/N MS20006-32

Description

Fastener Length: 2-11/16", Thread: 3/8-24, Head Width: 5/16", Thread Length: 11/16", internal wrenching, undrilled

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS2000632

Minimum Qty (MOQ):

NSN: 5306-00-206-5815

Schedule B: 7318.15.8085

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N MS20006-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Maximum
Fastener Length:	2.688 Inches Nominal
Head Style:	Bevel-conical Seven Seve
Head Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Head Height:	0.375 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.313 Inches Minimum And 0.315 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this internal wrenching bolt from our inventory online by visiting https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.