

# P/N MS20006-40

Military-Fasteners.com

#### Description

Fastener Length: 3-13/64", Thread: 3/8-24, Head Width: 5/16", Thread Length: 45/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | MS2000640                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-206-5816                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS20006-40 Specifications

| Thread Class:                                     | За   |
|---|--|
| Thread Direction:                                 | Right-hand   |
| Thread Length:                                    | 0.662 Inches Minimum And 0.712 Inches Maximum  |
| Fastener Length:                                  | 3.173 Inches Minimum And 3.203 Inches Maximum  |
| Head Style:                                       | Bevel-conical  |
| Head Diameter:                                    | 0.639 Inches Minimum And 0.649 Inches Maximum  |
| Head Height:                                      | 0.375 Inches Nominal   |
| Internal Drive Style:                             | Hexagon  |
| Nominal Thread Diameter:                          | 0.375 Inches   |
| Width Across Flats:                               | 0.313 Inches Minimum And 0.315 Inches Maximum  |
| Thread Quantity Per Inch:                         | 24   |
| Minimum Tensile Strength:                         | 160000 Pounds Per Square Inch  |
| Hardness Rating:                                  | 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| Material:   | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall   |
| Material Document And<br>Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material<br>Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:                                | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document<br>And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                         | Unf  |

### How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-40</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.