

**Description**

Fastener Length: 3-1/2", Thread: 3/8-24, Head Width: 5/16", Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS2000645                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-206-5811                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS20006-45 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.678 Inches Minimum And 0.698 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 3.485 Inches Minimum And 3.515 Inches Maximum                       |
| <b>Head Diameter:</b>                                 | 0.639 Inches Minimum And 0.649 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.375 Inches Nominal  |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Width Across Flats:</b>                            | 0.313 Inches Minimum And 0.315 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall       |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/internal+wrenching+bolts/MS20006-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.